XELTRON®

COLOR SORTERS

CONTACT US

www.xeltron.com

XELTRON®

COLOR SORTERS

OPTICAL GRAIN COLOR SORTER

XV-107

1 ton/hour

DESDE 1974

XV-107

TECHNICAL CHARACTERISTICS

UPPER HOPPER
- Provides an orderly and constant flow

RIBBED TRAY
- Low friction coefficient and high degree of coating
- Aligns the product avoiding agglomerations

INDUSTRIAL CAMERAS
- High-speed RGB HD technology and data exposure
- Highly sensitive to color variations

LED LIGHTS
- High fidelity and durability
- Low heat emission

Low energy consumption

INDUSTRIAL TOUCH SCREEN
- 15" high resolution dynamic multilingual interface
- User friendly configuration

XV - SOFTWARE
- Designed to be operated with minimal technical training
- High-precision, high-speed image analysis
- Frequent calibration storage space
- Self-adjustment and fault detection system

SOLENOID VALVE
- High and rapid ejection rate
- Low electricity consumption
- Service life in millions of cycles

TIME AND TEMPERATURE SENSORS
- Keeps track of maintenance cycles

X-CONNECT RSA (Remote System Analysis)
- Real time remote technical service

LOWER HOPPER

Easy access for accept and reject sampling

ADVANTAGES

- Operator friendly
- Extremely effective sorting primary, secondary, spotted, animal bitten, foreign and quaker defects
- Custom calibration support
- UPS included
- Low maintenance, power and compressed air consumption
- Local and real time Technical Support; spare part stock
- High Volume - Small Footprint

PRODUCTION

Varies depending on type and product contamination

MODEL	TRAYS	MINIMUN SORT Ton/hour	MAXIMUM SORT Ton/hora
XV-107	1	0.2	1

SIZE & CONSUMPTION

MODEL	COMPRESSED AIR / CFM Cubif feet per minute	ENERGY Kw/ h 220 VAC 60 HZ	WIDTH (meters)	DEPTH (meters)	HEIGHT (meters)
XV-107	3.6	0.35	0.43	1.43	2.05

XELTRON®
SELECCIONADORAS POR COLOR